



REDLINE 12-80 V DC

Červené svetlo pre označenie

EEW2015R
ECCO Red line 12-80 V

- 360 ° výstražná indikácia
- Extrémne odolné proti nárazom a vibráciám
- Polykarbonátová šošovka
- Hliníkové puzdro



POPIS PRODUKTU

ŠPECIFIKÁCIA

Battery	Nie
Color light	Červená
EMC	R10
Farba	Číra
Hmotnosť	0,27 kg
Materiál	Hliník
Number of LED	3 ks
Prevádzková teplota max.	50 °C
Prevádzková teplota min.	-30 °C
Šírka	62 mm
Svätelný tok	86 lm
Typ zdroja	Červená LED
Width base	74 mm
Voltage	12-80V
Výška	65 mm

DISCLAIMER

2-18 AWG WIRE
BLACK - NEGATIVE (-)
RED - POSITIVE (+)

SPECIFICATIONS

- CERTIFICATION: ETL E-List, C-List
- Note: Usage components, dimensions, and tolerance are not included in the Product Certification List. Certifications related to items are predicated upon the latest product model configuration.
- RAW LUMENS: 8 Lumens
- EFFECTIVE LUMENS: 45 Lumens
- PEAK BEAM INTENSITY: 1433 Candela
- EFFICIENCY: 18.7 lm/W
- CORRELATED COLOR TEMPERATURE: 5000K
- VOLTAGE: 12 VDC
- VOLTAGE (EXTREME): 9 to 16 VDC
- VOLTAGE (NOMINAL): 12 VDC
- CURRENT (PEAK): 1.65 A @ 12 VDC (NOMINAL)
- POWER (MAXIMUM): 13.2W @ 12 VDC (NOMINAL)
- TEMPERATURE RANGE: 20° F (0° C) TO 127° F (50° C)
- CONNECTION: 2 - 18 AWG WIRE CABLE
- MOUNTING BRACKET MOUNT
- MOUNTING MATERIAL: ALUMINUM
- LENS MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 34.185 (0.757 Kg)

DISCLAIMER: DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. EGGO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THE PRODUCT.

MOUNTING DISCLAIMER: MOUNTING MEASUREMENTS ARE FOR REFERENCE ONLY. MEASURE BEFORE DRILLING.

REV	DATE	DESCRIPTION	BY	CHK
01	01/11/2023	ISSUE FOR PRODUCTION	EGG0	EGG0

www.egg0.com

NOTE: 1. DIMENSIONS IN PARENTHESIS ARE FOR REFERENCE ONLY. 2. DIMENSIONS IN PARENTHESIS ARE FOR REFERENCE ONLY.

EGG0 ENGINEERING INC. 10000 15th Street, Suite 100, San Diego, CA 92128

2-18 AWG WIRE
BLACK - NEGATIVE (-)
RED - POSITIVE (+)

SPECIFICATIONS

- CERTIFICATION: ETL E-List, C-List
- Note: Usage components, dimensions, and tolerance are not included in the Product Certification List. Certifications related to items are predicated upon the latest product model configuration.
- RAW LUMENS: 8 Lumens
- EFFECTIVE LUMENS: 45 Lumens
- PEAK BEAM INTENSITY: 1433 Candela
- EFFICIENCY: 18.7 lm/W
- CORRELATED COLOR TEMPERATURE: 5000K
- VOLTAGE: 12 VDC
- VOLTAGE (EXTREME): 9 to 16 VDC
- VOLTAGE (NOMINAL): 12 VDC
- CURRENT (PEAK): 1.65 A @ 12 VDC (NOMINAL)
- POWER (MAXIMUM): 13.2W @ 12 VDC (NOMINAL)
- TEMPERATURE RANGE: 20° F (0° C) TO 127° F (50° C)
- CONNECTION: 2 - 18 AWG WIRE CABLE
- MOUNTING BRACKET MOUNT
- MOUNTING MATERIAL: ALUMINUM
- LENS MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 34.185 (0.757 Kg)

DISCLAIMER: DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. EGG0 ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THE PRODUCT.

MOUNTING DISCLAIMER: MOUNTING MEASUREMENTS ARE FOR REFERENCE ONLY. MEASURE BEFORE DRILLING.

REV	DATE	DESCRIPTION	BY	CHK
01	01/11/2023	ISSUE FOR PRODUCTION	EGG0	EGG0

www.egg0.com

NOTE: 1. DIMENSIONS IN PARENTHESIS ARE FOR REFERENCE ONLY. 2. DIMENSIONS IN PARENTHESIS ARE FOR REFERENCE ONLY.

EGG0 ENGINEERING INC. 10000 15th Street, Suite 100, San Diego, CA 92128