



Dopyt



TERMOČLÁNKY

Séria TC47-NT

TC47-NT
Termočlánok

- Teplota -40°C až 750°C
- K, J, K, T
- Telo nerez



POPIS PRODUKTU

ŠPECIFIKÁCIA

Prevádzková teplota max. 750 °C

Prevádzková teplota min. -40 °C



Nozzle bolt material <ul style="list-style-type: none"> ■ Stainless steel ■ Brass ■ Others on request 	Lead wire covering <ul style="list-style-type: none"> ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid
Junction <ul style="list-style-type: none"> ■ Grounded (unisolated) ■ Ungrounded (isolated) 	Termination at lead end <ul style="list-style-type: none"> ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 1G (male) ■ Lemosa plug size 2S (male) ■ Screw-in plug (Binder) (male) ■ Others on request
Nozzle bolt thread size <ul style="list-style-type: none"> ■ 1/4 x 28 ■ M5 ■ M8 ■ Others on request 	Calibration type <ul style="list-style-type: none"> ■ J ANSI MC96.1 red ⊕ white ⊖ ■ K ANSI MC96.1 red ⊕ yellow ⊖ ■ T ANSI MC96.1 red ⊕ black ⊖ ■ J IEC 584-3 white ⊕ black ⊖ ■ K IEC 584-3 white ⊕ green ⊖ ■ T IEC 584-3 white ⊕ brown ⊖ ■ J DIN 43714 blue ⊕ red ⊖ ■ K DIN 43714 green ⊕ red ⊖ ■ T DIN 43714 brown ⊕ red ⊖ ■ Others on request
Lead length <ul style="list-style-type: none"> ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request 	
Lead wire <ul style="list-style-type: none"> ■ Fibreglass / Fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request 	