



TERMOČLÁNKY

Séria TC47-AC

TC47-AC Termočlánek

- Teplota -40°C až 750°C
- K, J, K, T
- Telo nerez



POPIS PRODUKTU

ŠPECIFIKÁCIA

Prevádzková teplota max. 750 °C

Prevádzková teplota min. -40 °C

Adjustable compression version <ul style="list-style-type: none"> ■ Straight ■ 45° bend ■ 90° bend 	
Junction <ul style="list-style-type: none"> ■ Grounded (unisolated) ■ Ungrounded (isolated) 	
Probe diameter <ul style="list-style-type: none"> ■ 3/16" ■ 1/4" ■ 3/8" ■ 4 mm ■ 6 mm ■ 8 mm ■ Others on request 	
Probe length <ul style="list-style-type: none"> ■ Standard: 100 mm (4") ■ Others on request 	
Compression fitting material <ul style="list-style-type: none"> ■ Brass ■ Stainless steel ■ None 	
Thread size <ul style="list-style-type: none"> ■ Thread size on request 	
Lead length <ul style="list-style-type: none"> ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request 	
Lead wire <ul style="list-style-type: none"> ■ Fibreglass / Fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request 	
Lead wire covering <ul style="list-style-type: none"> ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour 	
Termination at lead end <ul style="list-style-type: none"> ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 15 (male) ■ Lemosa plug size 25 (male) ■ Screw-in plug, Binder (male) ■ Others on request 	
Calibration type <ul style="list-style-type: none"> ■ J ANSI MC96.1 red ⊕ white ⊕ ■ K ANSI MC96.1 red ⊕ yellow ⊕ ■ T ANSI MC96.1 red ⊕ blue ⊕ ■ J IEC 584-3 white ⊕ black ⊕ ■ K IEC 584-3 white ⊕ green ⊕ ■ T IEC 584-3 white ⊕ brown ⊕ ■ J DIN 43714 blue ⊕ red ⊕ ■ K DIN 43714 green ⊕ red ⊕ ■ T DIN 43714 brown ⊕ red ⊕ ■ Others on request 	